

THE FOLLOWING IS CLAIMED:

1). A laminar structure comprising at least one mastic layer, at least a portion of the mastic layer in contact with at least one UV and moisture resistant barrier film or layer and optionally at least one release film or layer.

2). A shaped non-conductive laminar structure consisting essentially of at least one elastomeric layer, at least one polyethylene film or layer and at least one removable release film or layer.

3). A substrate comprising at least one of wood or metal wherein the structure of Claim 1 or 2 is attached to at least one surface of the substrate.

4). The structure of Claim 1 wherein the mastic layer comprises butyl rubber, polybutene and at least one filler.

5). The structure of Claim 4 wherein filler comprises at least one member from the group consisting of calcium carbonate, clay, aluminum stearate, silicon dioxide and titanium dioxide.

6). The structure of Claim 1 wherein UV barrier film or layer comprises opaque low density polyethylene.

7). The structure of Claim 1 or 2 wherein said release layer comprises high density polyethylene.

8). The structure of Claim 1 wherein said structure further comprises at least one anti oxidant.

9). The structure of Claim 1 wherein said structure has a dielectric strength of greater than 235 V/Mil.

10). The structure of Claim 1 wherein said structure has a tensile adhesive strength of at least 17 psi.

11). The structure of Claim 2 wherein said elastomeric layer comprises about 75 to about 90 wt.% of at least one additive.

12). The structure of Claim 11 wherein said additive comprises at least one member selected from the group consisting of butyl rubber, butyl-styrene rubber and polyisobutylene rubber.